



Features

- High intensity audible sounder: produces a loud tone every 2 seconds as long as the logger reports an alarm state.
- Works with temperature and RH loggers
- Clear alarms button: resets logger's alarm
- Test button
- Programmable delay: 1 minute to 11 days (using free software)
- Two sets of volt-free relay contacts for interfacing to other devices
- Audible battery low warning: three rapid pips repeated once a minute
- Long battery life
- Battery Included

Approvals

This equipment complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause any harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This product is manufactured by Gemini Data Loggers (UK) Ltd to BS EN ISO 9001:2000 (Certificate No. 6134), and CE approved to EN50081 part 1:1992 and EN50082 part 1:1992 with any standard leads supplied.



Mechanical Data

Case Dimensions

- Height : 115mm / 4.43"
- Width : 105mm / 4.13"
- Depth : 33mm / 1.3"
- Weight : 220g / 7.8 oz. including Battery.

Specifications

- Temp. Range : 0°C to 55°C
32°F to 131°F
- Relative Humidity : 0 to 90% non-Condensing
- Battery Type : 9V Alkaline PP3, AM6, MN1604, 6LR61, 6F22, or equivalent
- Battery Life : up to 2 years standby use,
5 days of continuous alarms.

Interface Information and Related Products

To use your alarm unit you will need a suitable cable (CAB-0012 supplied with unit) and one of the following Data Loggers:

TG12-0017	TG12-0020	TGP-0017	TGP-0020	TGP-0050	TGP-0073	TGP-0104
TGP-0204	TGP-0304	TGP-1500	TGP-1510	TGP-1515	TGP-1520	TV-0020
TV-0050	TV-0073	TV-0076	TV-0104	TV-0204	TV-0304	TV-1500
TV-1510	TV-1515					

To use the delay feature you will need to install a software tool which is a free add-on for Gemini Logger Manager (GLM) software.